



單位Unit : mm

品 號	止 輪 尺 寸 Ring Dimension						適用軸尺寸 Shaft Dimension (Reference Only)					
	d		D	b	t		d ₁	d ₂		m		n
Ring No.	扣環內徑 Free Dia.	公差 Tol.	扣環直徑 Clearance Dia.	寬度 App.	厚度 Thickness	公差 Tol.	軸直徑 Shaft Dia.	溝槽直徑 Groove Dia.	公差 Tol.	溝槽寬 Width	公差 Tol.	最小 Min.
CT- 12	2.59	+0.05 -0.1	4.17	0.79	0.4	±0.03	3.2	2.69	±0.04	0.48	+0.04	0.5
18	4.09		6.19	1.05	0.4		4.8	4.19		0.48	-0	0.6
21	4.75	+0.07 -0.13	6.99	1.12	0.6	±0.04	5.6	4.9	±0.05	0.7	+0.06 -0	0.7
25	5.36		7.90	1.27	0.6		6.4	5.59		0.7		0.8
31	6.86		9.56	1.35	0.6		7.9	7.01		0.7		0.9
37	8.33		11.37	1.52	0.6		9.5	8.51		0.7		1.0
40	9.12		12.32	1.60	0.6		10.3	9.25		0.7		1.1
43	9.8		13.10	1.65	0.6		11.1	9.98		0.7		1.1
46	10.54	±0.15	14.00	1.73	0.6	±0.05	11.9	10.69	±0.07	0.7	+0.08 -0	1.2
50	11.2		14.76	1.78	0.9		12.7	11.43		1.0		1.3
56	12.62		16.56	1.98	0.9		14.3	12.88		1.0		1.4
62	14.05		18.16	2.06	0.9		15.9	14.3		1.0		1.6
81	18.31	±0.18	23.23	2.46	1.4	±0.06	20.6	18.59		1.5		2.3

*未顯示於表格之規格歡迎來電洽詢

*Other sizes may be available upon request

Copyright (c) 2024 MK Spring Co., Ltd. All Rights Reserved

✓ 規格標準 Standard Reference

WALDES TRUARC, series 5103

Arcon, series N1800

✓ 材質、硬度 & 表面處理 Material, Hardness Ranges & Finish

材質 Material	硬度 Hardness Ranges	表面 Finish
彈簧鋼 SAE1050~SAE1090 Carbon Spring Steel	HRC 44-53 (Rockwell scale)	染黑 Black Oxide
		鍍鎳 Nickel Plating
不鏽鋼 SUS301 & SUS304 Stainless Steel Type 301 & 304	HV 250-420 (Vickers scale)	原色 Plain
不鏽鋼 SUS420 Stainless Steel Type 420	HRC 44-52 (Rockwell scale)	原色 Plain

✓ 包裝方式 Packaging

散裝 Bulk

條裝 Stacked

*條裝包裝僅少量現貨供應 Not all sizes in stacked in stock